KOZ°PRODUCTS≧

SPECIFICATION KOZ TYPE B-TOOL S

Application:	The KOZ B-tool S is the tool to assemble KOZ cable clamps and blocks on a straight or round pole, without damaging them by e.g. drilling or sawing. The KOZ B-tool S can also be used to install other products on straight or round poles.				
Range:	B-tool S is suitable for: KOZ ST 18-26, 26-38, 36-52, 50-75 KOZ STC 21-38, 36-52, 46-75 KOZ TRI eco 24-35, 33-46, 47-66 KOZ UNI 3x 13-32, 4x 13-32, 3x 30-49, 4x 30-49, 3x 45-67 KOZ SQ 28, 25-35				
Material:	Black polyamide (PA66), fibreglass-reinforced, virgin material.				
Fire resistance:	UL94 V-0 and classification standard DIN 5510-2:2009 with flammability class S3, smoke SR2 and dripping ST-2.				
Temperature:	Permanent application from -80°C to +120°C. Short-term heating of up to +220°C.				
Advantages:	Resistant to oils, greases, frost, heat, UV, ozone, salt water, salts, acids, aggressive chemicals and radioactive radiation. Non-oxidizing, non-corrosive, non-magnetic and non-conductive. Halogen-free and no sharp edges. Lifetime warranty, easy assembly and available worldwide.				
Extra possibilities:	B-tools can be assembled by using a steel tie ("Bandit band"). You can turn the B-tool inside or outside, depending on the outer diameter of the cable.				



DIMENSIONS IN MILIMETERS						
Туре	L	В	I	D	S	Н
KOZ B-tool S	60	35	12,5	5	26-2	32

NO RIGHTS MAY BE DERIVED FROM THIS DOCUMENT. KOZ PRODUCTS B.V. RESERVES THE RIGHT TO IMPLEMENT ANY CHANGES WITHOUT NOTICE. SEE OUR WEBSITE FOR MORE INFORMATION. NO PART OF THIS PUBLICATION MAY BE REPRODUCED OR USED FOR OTHER PURPOSES WITHOUT KNOWLEDGE OR SPECIFIC PERMISSION OF KOZ PRODUCTS B.V.